

LED Linear Wall Light Double

Model: KRLINWALLDB500/600/700

LED Architectural light for walls, bathrooms, accent lighting, etc.

Certification:

Meets AS/NZS 61347 Contained in ENEC and SAA
LM-79, LM-80, TM-21, CE, ROHs, TUV



LM-79

LM-80



Applications

Available in 500mm, 600mm and 700mm lengths
Available in 16w, 20w and 24w
Replaces traditional Fluorescent fixtures
High efficiency LEDs used
Energy saving than T5
Energy saving over T8
Operating temp: -20C to +60C
Lifetime: > 50,000hrs to L70
Warranty: 5 years

Technical Characteristics

Source: Taiwanese LEDs
Voltage: 85-285V AC
Power factor: > 0.95
Efficiency: > 0.91
Depreciation: < 1 % at 6000hrs @55C
Color: 2700K, 3000K, 3500K, 4000K
Color rendering (MacAdam)
CRI (CRI Available > 95ra)

Model Codes:

- KRLINWALLDB500: 16w ~1,600 Lumens
- KRLINWALLDB600: 20w ~1,600 Lumens
- KRLINWALLDB700: 24w ~2,000 lumens

Add:

- "-DALI" for Dali dimming
- "-110V" for 1-10v dimming
- "-DIM" for standard dimming
- "-Black" or "-White" or "-Silver" for body colour

