

LED Slimline Surface Fixture

Model: KRLSU16W/32W/40W

LED light with broad beam for surface mounting

Extremely low profile (23mm)



Certification:


Meets AS/NZS 61347 Contained in ENEC and SAA

LM-79, LM-80, TM-21, CE, ROHs, TUV



LM-79

LM-80



Specifications

> 150lm/cw Overall Efficiency

Integrated Microwave Sensor Option with Pre-set or remote adjustable version available

Working temp. -20C to +60C

Lifetime >120,000hrs to L70

IP44 Ingress Protection

Warranty 5 years

Modular system bracket system allows multiple units to mount side by side

Model Codes:

- KRLSU16W 600mm length ~ 2,400 lumens
- KRLSU32W 1200mm length ~ 4,800 lumens
- KRLSU40W 1500mm length ~ 6,000 lumens
- KRLSU60W 1500mm length ~ 9,000 lumens

Meanwell Driver as standard

Add:

- "-DALI" for Dali dimming
- "-110V" for 1-10V dimming
- "-DIM" for standard dimming
- "-Black" or "-White" for body colour

Electrical Characteristics

- Light Source: Taiwanese LEDs
- Input Voltage: 85-285V AC
- Power Factor: > 0.95
- Driver Efficiency: > 0.91
- Lumen Deprecation: < 1 % at 6000hrs @55C
- CCT: 2700K, 3000K, 3500K, 4000K
- (3-Step MacAdam)
- CRI: > 85ra (CRI Available > 95ra)

Applications

Allows for installation on low ceilings giving excellent dispersion of light and high uniformity

Extremely High Efficiency LEDs to maximise savings ver Fluorescent fixtures

Available with suspension hanging kit for pendent mounting

KRLSU32W 1200mm length (replaces 2x36w 4ft T8)

KRLSU40W 1500mm length (replaces 2x58w 5ft T8)